

PRODUCT INFORMATION

Item Number	7552
Product Colour	Yellow
Size Range	22 inch
Primary Coating Polymer	Uncoated
Grip	Uncoated
Cut Score	C
Heat Resistance	Contact Heat Level 2

FEATURES

Heat Resistant: Achieves Level 2 for Contact Heat according to EN407. Can withstand temperatures of 250°C
100% Kevlar® aramid fibre offers increased resistance to heat

Cut Resistant: Achieves cut level C according to EN388, for protection in high risk cut hazard applications.

Cut Resistant: Kevlar® provides increased protection against cuts, slashes and abrasion, while maintaining a high degree of dexterity for the wearer

Unique Feature: Machine washable to extend life

Abrasion Resistant: Achieves Level 2 for abrasion resistance as defined by European Standard EN388

SECTORS

Automotive • Construction and Utility • Engineering and Manufacturing • Warehousing, Transport, and Logistics

STANDARDS



PPE CAT II



2X4XC



X2XXXX



CAUTION

May contain latex in elasticated cuff which can cause allergic reactions, including anaphylactic response.

STORAGE INSTRUCTIONS

Store in dry conditions, away from direct sunlight and extreme heat. It is recommended to retain the packaging for reference. Always inspect gloves prior to use and do not use if damaged or showing signs of wear and tear.

DISPOSAL INSTRUCTIONS

Dispose of the product responsibly in accordance with local regulations.

PACKING

24 sleeves per polybag
96 sleeves per case
30 cases per pallet

OUTER PACKAGING BARCODE

05010699809117

For further technical information, please contact Customer Services on 0333 320 8550 or the Technical team on 0333 320 8555