

## PRODUCT INFORMATION

Item Number	AFG41-1
Size Range	7-12
Primary Coating Polymer	Latex
Max Working AC Voltage	7500.00 V

## FEATURES

**Electrical Handling:** Class 1, for a maximum working AC voltage of 7500V  
**Arc flash Class 1** according to EN 61482-1-2, with an ATPV of 42.2 cal/cm<sup>2</sup>

**Electrical Insulating glove 3 in 1:** dielectric, mechanical and arc flash protection

**Length:** 41cm length for extended protection up the arm

**Electrical Handling:** Internal black/external red to make visual inspection easier

Each pair of gloves is supplied with a pair of cotton fingerless under gloves for improved comfort

Unique formulation of the rubber compound makes gloves extremely flexible

**Chemical Resistant:** Passes special properties 'RC' for protection against acid, oil, ozone and extremely low temps

## SECTORS

Automotive • Engineering and Manufacturing • Oil, Gas, and Renewables • Warehousing, Transport, and Logistics

## STANDARDS



Class 1/RC



## CAUTION

Contains latex which may cause allergic reactions, including anaphylactic response.

Contains accelerator chemicals which may cause type IV skin irritation and contact dermatitis in sensitised individuals.

## STORAGE INSTRUCTIONS

Store in dry conditions, away from direct sunlight and extreme heat. It is recommended to retain the packaging for reference. Always inspect gloves prior to use and do not use if damaged or showing signs of wear and tear.

## DISPOSAL INSTRUCTIONS

Dispose of the product responsibly in accordance with local regulations.

## PACKING

1 pair per bag

For further technical information, please contact Customer Services on 0333 320 8550 or the Technical team on 0333 320 8555

Size	Outer Packaging Barcode
7	<b>3760245125179</b>
8	<b>3760245125186</b>
9	<b>3760245125193</b>
10	<b>3760245125209</b>
11	<b>3760245125216</b>
12	<b>3760245125223</b>

For further technical information, please contact Customer Services on 0333 320 8550 or the Technical team on 0333 320 8555