



PRODUCT INFORMATION

Item Number	RE3360
Size Range	8-12
Primary Coating Polymer	Latex
Max Working AC Voltage	26500.00 V

FEATURES

Electrical Handling: Class 3, for a maximum working AC voltage of 26500V

Length: 36cm length for protection up the wrist

Flexibility: Industry leading latex manufacturing techniques and expertise allows gloves to be as soft and thin as possible offering the maximum level of the dexterity to the user

Chemical Resistant: Passes special properties 'AZC' for protection against acid, ozone and extremely low temps

Electrical Handling: Designed to be used in conjunction with our leather Protector Gauntlet (RE-PRO & RE-PRO/NB) for additional longevity and mechanical protection
Excellent electrical resistance

Lining: Lightly powdered to ensure easy donning and doffing

SECTORS

Automotive • Construction and Utility

STANDARDS



PPE CAT III



Class 3/AZC



0333



CAUTION

Contains latex which may cause allergic reactions, including anaphylactic response.
Contains accelerator chemicals which may cause type IV skin irritation and contact dermatitis in sensitised individuals.

STORAGE INSTRUCTIONS

Store in dry conditions, away from direct sunlight and extreme heat. It is recommended to retain the packaging for reference. Always inspect gloves prior to use and do not use if damaged or showing signs of wear and tear.

DISPOSAL INSTRUCTIONS

Dispose of the product responsibly in accordance with local regulations.

PACKING

1 pair per bag
280 pairs per pallet

For further technical information, please contact Customer Services on 0333 320 8550 or the Technical team on 0333 320 8555

Size	Outer Packaging Barcode
8	05010699855572
9	05010699855589
10	05010699855596
11	05010699855602
12	05010699542106

For further technical information, please contact Customer Services on 0333 320 8550 or the Technical team on 0333 320 8555