

characteristics Cleanroom Stool 3 with glides and footring

Article: 9461R integral foam

Dimensions in mm

Seat:	H:	560 - 830
	B:	400
	T:	400
Packing data	Weight	kg 8,92
	Volume	m ³ 0,09

**Base equipment**

		Benefit
Suitable for cleanrooms	Air cleanliness class 3 according to DIN EN ISO 14644-1 Sealed upholstery with foam backing technology Materials suitable for cleanrooms Smooth, sealed surfaces	Certified suitability for clean rooms Any particle emissions are reliably avoided Deposits of particles on the stool are prevented.
Conductivity	Steel parts with a conductive coating Comfortable, conductive upholstery Typical leakage resistance of 106 ohm Volume-conductive castors	Exceeds the ESD requirements of DIN EN 61340-5-1. Complete ESD safety.
Seat	Extra-large seat with a diameter of 400 mm. Extra-strong and soft 60 mm comfort upholstery.	Automatically encourages a correct sitting posture and upright, healthy sitting. The rounded front edge of the seat prevents possible blood congestion in the thighs.
Soft cover	Soft cover underneath the seat	The ring release and the mechanism disappear underneath the soft cover. This prevents particles from being released. Dust does not accumulate and cleaning becomes easy and efficient.
Seat design	Integral foam upholstery (PU): The integral foam pad offers maximum resistance and ease of cleaning. Extremely robust, durable, washable, disinfectant-proof, PVC-free, resistant to blood and urine, fire protection in accordance with EN 1021 Parts 1 + 2, black colour.	Recommended use in environments where staff come into contact with aggressive working materials. The surface is resistant, extremely robust, washable and easy to clean. Resistant to pointed and sharp objects.
Seat height	Infinitely variable seat height adjustment from 560-830 mm by gas spring with protective cover.	Large seat height adjustment range. The cover protects the gas spring against dust and dirt.
Technology	Ring release	Easy and convenient height adjustment from any sitting position thanks to a ring release underneath the seat.
Base	Particularly small aluminium base with a diameter of 54 cm.	Space-saving and high mobility due to the available legroom.
Castors/glides	Wearproof plastic glides with a large surface area.	Offer a superb level of stability
Foot ring	Height adjustable, chrome-plated foot ring.	Wide foot plate provides good support. Height can be quickly and easily adjusted.

characteristics Cleanroom Stool 3 with glides and footring

Article: 9461R integral foam

Dimensions in mm

Seat:	H:	560 - 830
	B:	400
	T:	400
Packing data	Weight	kg 8,92
	Volume	m ³ 0,09



Material used

All materials can be recycled separately.

Environmentally friendly

Standards	DIN 68 877 EN ISO 14644-1 DIN EN 61340-5-1 GS certificate for "tested safety" DIN EN ISO 9001 quality management DIN EN ISO 14001 environmental management EMAS tested environmental management OHSAS 45001 occupational health and safety management EcoVadis CSR rating 20 Gold	Procurement security
Warranty	10-year long-term warranty, with 3-year full warranty	Free shipping of replacement parts within the entire period.