

Screw-in Plugs GPN 550



www.poeppelmann.com/en/gpn550


Application

The GPN 550 screw-in plugs offers protection for threads and bore holes against dirt and damage and are particularly suitable for painting. The thick-walled shaft can be screwed into threads in a self-tapping manner. The conical shape of the screw-in plugs allows tolerances to be accommodated.

All information about 100% PCR and the recycling blend can be found in "Sustainability at Pöppelmann" (see chapter 2) or at www.poeppelmann.com/en/kapsto/Responsibility.html



www.blauer-engel.de/uz30a



PCR-PE
blue



PCR-PE / PE-LD
yellow



PE-LD
yellow

Article	Thread	A	B	C	H	M	100% PCR	Recycling blend	Virgin material
GPN 550 / 002	M 2	7	1,3	2	7	14	5500002RB61	55000020073	55000020000
GPN 550 / 003	M 3	7	2,1	3	12	19			55000030000
GPN 550 / 004	M 4	8	2,8	4	15	22	5500004RB61	55000040073	55000040000
GPN 550 / 005	M 5	9	3,6	5	18	27	5500005RB61	55000050073	55000050000
GPN 550 / 006	M 6	11	4,3	5,8	18	27	5500006RB61	55000060073	55000060000
GPN 550 / 007	M 7	10,5	5	6,5	18	27	5500007RB61	55000070073	55000070000
GPN 550 / 008	M 8	14	6	7,5	18	27	5500008RB61	55000080073	55000080000
GPN 550 / 009	M 9	14	6,5	8,5	18	27	5500009RB61	55000090073	55000090000
GPN 550 / 010	M 10	16	7,6	9,3	21	30	5500010RB61	55000100073	55000100000
GPN 550 / 012	M 12	18	9,3	11,3	21	30	5500012RB61	55000120073	55000120000

Dimensions in mm.

Information on materials, colours, designs and use of our products can be found on the website and in chapter 3 'Materials and application'.

The articles in the 100% PCR column consist of 98% PCR-PE and 2% colour based on a PIR carrier. The plastic used consists of 100% PCR.

The articles in the recycled mixture column consist of a blend of PCR and virgin material. Colour deviations and black dots cannot be completely avoided during production and are permissible for these items. We recommend carrying out functional tests before series production.

Your added values:



More resource-saving.

This standard series is available from PCR, saves CO2e emissions and conserves resources.



More robust.

Thick-walled shaft for increased demands.



More versatile.

Tapered plug to accommodate tolerances.



Better.

Self-tapping plug for tight closure of threads or bore holes. Ideal for painting processes.