

## characteristics ESD saddle stool with castors

Article: 9473E fabric

Dimensions in mm

Seat:	H:	540-800
	B:	350
	T:	415

Packing data	Weight	kg	8,5
	Volume	m <sup>3</sup>	0,09



Base equipment		Benefit
Conductivity	Steel parts with a conductive coating Comfortable, conductive upholstery Typical leakage resistance of 10 <sup>6</sup> ohm Volume-conductive castors	Exceeds the ESD requirements of DIN EN 61340-5-1. Complete ESD safety.
Seat	Comfortable saddle seat	Promotes an ergonomic sitting posture that supports the natural S-shape of the spine.
Seat design	3-zone upholstery foam	For optimum pressure distribution and seating comfort.
	Duotec fabric upholstery: Hard-wearing, breathable and comfortable seat cover. Fire protection in accordance with EN 1021 Part 1, colour: Black.	The upholstery is breathable and can absorb and release moisture. Maximum seating comfort is guaranteed thanks to the particularly soft surface.
Seat height	Infinitely variable seat height adjustment from 540-800 mm by gas spring with protective cover.	Extra-large seat height range. Can be customised to suit the workstation and user The perfect solution for raised workstations that require mobility or only offer limited legroom
Technology	3D seat dynamics	Intuitive 3D seat dynamics to ensure active, dynamic sitting
Base	Particularly small aluminium base with a diameter of 54 cm.	Space-saving and high mobility due to the available legroom.
Castors/glides	Large castors with a diameter of 65 mm. Move smoothly.	Stools are braked when not used which decreases the risk of accidents.
Material used	All materials can be recycled separately.	Environmentally friendly
Standards	DIN 68 877 Procurement security DIN EN 61340-5-1 GS certificate for "tested safety" DIN EN ISO 9001 quality management DIN EN ISO 14001 environmental management EMAS tested environmental management OHSAS 45001 occupational health and safety management EcoVadis CSR rating 20 Gold	Procurement security
Warranty	10-year long-term warranty, with 3-year full warranty	Free shipping of replacement parts within the entire period.